

## SPECIFICATION FOR MD-DFM152

Panel size/type	15" TFT active matrix LCD, anti-glare and hard coated
Pixel dimension	0.297mm x 0.297mm
Native/ Optimum resolution	1024 x 768
Response time	8 ms
Contrast ratio	700:1
Brightness	250 cd/m <sup>2</sup>
View angle	Hor: 60 to 60 deg Ver: 40 to 60 deg
Display color	262K
Active display area	304.128 mm x 228.096mm
Digital input	Standard DVI connector.
Analog input	Video: 0.7Vpp/75 ohm, Sync: Separate TTL level, composite Sync or Sync on Green, Hor: 30~80KHz, Ver: 50~75Hz
Compatible Digital Analog	DVI, up to VESA 1024 X <a href="#">768@75/70/60Hz</a> , VESA 800 X <a href="#">600@75/72/60/56Hz</a> , VESA 640 X <a href="#">480@75/72/60Hz</a> , Super VGA, VGA, Mac 832 x <a href="#">624@75Hz</a> , Power Mac and more.
External connector	Digital input: DVI-D*1, analog input: 15-D-sub*1, Power : DC in, audio
Cables	15 pin D-sub cable, EU power cord, DVI cable, audio cable
Plug & play	VESA DDC2B
User control and indicator	Dial control*1 for Power and multi-language OSD, Power indicator*1 Pre-Vu OSD: contrast, brightness, auto adjust, clock, phase, color temp, hor position, ver position, input select(digital / analog), key lock.
Base stand	Tilt and pivot two ways adjustable
Dimension (w*h*d)	375mm x 356mm x 210mm
Weight	Net: 5.3 kg
Power supply (AC/DC adaptor)	Input:100~240Vac, 1.5A, 60/50Hz, universal. Output: 12Vdc, 3A.
Power consumption	On: <27W; active off: <5W.
Power management	EPA Energy Star compliant
Agency approval RTD550AM	UL60601-1, CSAC22.2 NO.601.1, TUV(EN60601-1), FCC, CE.
Speaker (stereo)	1W X 2 (L/R)